

<b>1.</b>	<b>VESSEL DESCRIPTION</b>		
1.1	Date updated:	Aug 31, 2018	
1.2	Vessel's name:	MTM Newport	
1.3	IMO number:	9774575	
1.4	Vessel's previous name(s) and date(s) of change:	Not Applicable	
1.5	Date delivered:	Aug 24, 2018	
1.6	Builder (where built):	Shin Kurushima Dockyard Co. Ltd. / Japan	
1.7	Flag:	Singapore	
1.8	Port of Registry:	Singapore	
1.9	Call sign:	9V5429	
1.10	Vessel's satcom phone number:	+1 9044148678 /+ 88167777368 / +1 9044504530	
	Vessel's fax number:	NA	
	Vessel's telex number:	NA	
	Vessel's email address:	master@newport.cruisecontrolmail.com	
1.11	Type of vessel:	Oil/Chemical Tanker	
1.12	Type of hull:	Double Hull	
<b>Classification</b>			
1.13	Classification society:	Nippon Kaiji Kyokai	
1.14	Class notation:	NK NS* (CSR, Tanker, Oils Flashpoint on and below 60°C and Chemicals Type II & III, PSPC-WBT,NC) (ESP)(IHM) MNS*	
1.15	If Classification society changed, name of previous society:	N/A	
1.16	If Classification society changed, date of change:	N/A	
1.17	IMO type, if applicable:	Type II & III	
1.18	Does the vessel have ice class? If yes, state what level:	No,	
1.19	Date / place of last dry-dock:	24 August 2018	Shin kurushima Dockyard Co., Ltd.
1.20	Date next dry dock due	23 August 2021	
1.21	Date of last special survey / next survey due:	N/A	23 August 2023
1.22	Date of last annual survey:	N/A	
1.23	If ship has Condition Assessment Program (CAP), what is the latest overall rating:	NA	
1.24	Does the vessel have a statement of compliance issued under the provisions of the Condition Assessment Scheme (CAS): If yes, what is the expiry date?	N/A	
<b>Dimensions</b>			
1.25	Length Over All (LOA):	179.53 Metres	
1.26	Length Between Perpendiculars (LBP):	172.00 Metres	
1.27	Extreme breadth (Beam):	27.40 Metres	
1.28	Moulded depth:	16.30 Metres	
1.29	Keel to Masthead (KTM) / KTM in collapsed condition (if applicable):	43.84 Metres	
1.30	Bow to Center Manifold (BCM) / Stern to Center Manifold (SCM):	89.13 Metres	90.40 Metres
1.31	Distance bridge front to center of manifold:	60.64 Metres	
1.32	Parallel body distances:	Lightship	Normal Ballast Summer Dwt
	Forward to mid-point manifold:	33.02 Metres	34.88 Metres 34.88 Metres
	Aft to mid-point manifold:	26.45 Metres	36.68 Metres 51.73 Metres
	Parallel body length:	59.47 Metres	71.56 Metres 86.61 Metres
1.33	FWA at summer draft / TPC immersion at summer draft:	260 Millimetres	43.12 Metric Tonnes
1.34	What is the max height of mast above waterline (air draft)	Full Mast	Collapsed Mast
	Lightship:	41.12 Metres	0 Metres
	Normal ballast:	37.47 Metres	0 Metres
	At loaded summer deadweight:	32.233 Metres	0 Metres
<b>Tonnages</b>			
1.35	Net Tonnage:	10,288	
1.36	Gross Tonnage / Reduced Gross Tonnage (if applicable):	21,238	

**INTERTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 (Q88)**

1.37	Suez Canal Tonnage - Gross (SCGT) / Net (SCNT):		22,337.67	19677.25	
1.38	Panama Canal Net (PCNT):		17713		
<b>Loadline Information</b>					
1.39	Loadline Annex I	Freeboard	Draft	Deadweight	Displacement
	Summer:	4.728 Metres	11.607 Metres	35976 Metric Tonnes	44,861 Metric Tonnes
	Winter:	4.969 Metres	11.366 Metres	34,939 Metric Tonnes	43,824 Metric Tonnes
	Tropical:	4.487 Metres	11.848 Metres	37017 Metric Tonnes	45,902 Metric Tonnes
	Lightship:	13.750 Metres	2.585 Metres		8,885 Metric Tonnes
	Normal Ballast Condition:	9,930 Metres	6.41 Metres	14,448 Metric Tonnes	23,333 Metric Tonnes
1.40	Does vessel have multiple SDWT?			NO	
1.41	If yes, what is the maximum assigned deadweight?			NA	
<b>Ownership and Operation</b>					
1.42	Registered owner - Full style:	MTM Newport Pte. Ltd. 78 Shenton Way, #13-01, Singapore 079120 Tel: +65 63041770 Fax: +65 62207988 Email: marine@mtmsm.com			
1.43	Technical operator - Full style:	M.T.M. Ship Management Pte. Ltd. 78 Shenton Way, #13-01, Singapore 079120 Tel: +65 63041770 Fax: +65 62207988 Email: marine@mtmsm.com Web: www.mtmshipmanagement.com Company IMO#: 1314037			
1.44	Commercial operator - Full style:	M.T. Maritime Management (USA) LLC 2960 Post Road   Southport, CT 06890, USA Tel: +1 203 226-7882 Fax: +1 203 226-8934 Email: operations@mtmaritime.com Web: www.mtmaritime.com			
1.45	Disponent owner - Full style:	MTM Trading LLC Trust company complex , Ajeltake Island,Ajeltake Road, Majuro ,Marshall Islands MH 96960			
<b>2.</b>	<b>CERTIFICATION</b>	<b>Issued</b>	<b>Last Annual or Intermediate</b>	<b>Expires</b>	
2.1	Safety Equipment Certificate:	24-Aug-2018	Not Applicable	23-Jan-2019	
2.2	Safety Radio Certificate:	24-Aug-2018	Not Applicable	23-Jan-2019	
2.3	Safety Construction Certificate:	24-Aug-2018	Not Applicable	23-Jan-2019	
2.4	Loadline Certificate:	24-Aug-2018	Not Applicable	23-Jan-2019	
2.5	International Oil Pollution Prevention Certificate (IOPPC):	24-Aug-2018	Not Applicable	23-Jan-2019	
2.6	Safety Management Certificate (SMC):	24-Aug-2018	Not Applicable	23-Feb-2019	
2.7	Document of Compliance (DOC):	28-Jun-2017	Nov 22, 2017	16-Sep-2021	
2.8	USCG (specify: COC, LOC or COI): COC	Not Applicable	Not Applicable	Not Applicable	
2.9	Civil Liability Convention Certificate (CLC):	24-Aug-2018		20-Feb-2019	
2.10	Civil Liability for Bunker Oil Pollution Damage Convention Certificate (CLBC):	24-Aug-2018		20-Feb-2019	
2.11	U.S. Certificate of Financial Responsibility (COFR):	Not applicable		Not applicable	
2.12	Certificate of Fitness (Chemicals):	24-Aug-2018	Not Applicable	23-Jan-2019	
2.13	Certificate of Fitness (Gas):	Not Applicable	Not Applicable	Not Applicable	
2.14	Certificate of Class:	24-Aug-2018	Not Applicable	23-Jan-2019	

**INTERTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 (Q88)**

2.15	International Ship Security Certificate (ISSC):	24-Aug-2018	N/A	23-Feb-2019
2.16	International Sewage Pollution Prevention Certificate (ISPPC)	24-Aug-2018		23-Jan-2019
2.17	International Air Pollution Prevention Certificate (IAPP):	24-Aug-2018	Not Applicable	23-Jan-2019

**Documentation**

2.18	Does vessel have all updated publications as listed in the Vessel Inspection Questionnaire, Chapter 2- Question 2.24, as applicable:	Yes
2.19	Owner warrant that vessel is member of ITOPF and will remain so for the entire duration of this voyage/contract:	Yes

<b>3.</b>	<b>CREW MANAGEMENT</b>		
3.1	Nationality of Master:	MYANMAR	
3.2	Nationality of Officers:	MYANMAR	
3.3	Nationality of Crew:	MYANMAR	
3.4	If Officers/Crew employed by a Manning Agency - Full style:	Officers: N/A, Directly employed by Technical Operator Crew: N/A, directly employed by Technical Operator	
3.5	What is the common working language onboard:	ENGLISH	
3.6	Do officers speak and understand English:	Yes	
3.7	In case of Flag Of Convenience, is the ITF Special Agreement on board:	Yes	

<b>4.</b>	<b>HELICOPTERS</b>		
4.1	Can the ship comply with the ICS Helicopter Guidelines:	No	
4.2	If Yes, state whether winching or landing area provided:	NA	

<b>5.</b>	<b>FOR USA CALLS</b>		
5.1	Has the vessel Operator submitted a Vessel Spill Response Plan to the US Coast Guard which has been approved by official USCG letter:	Yes	
5.2	Qualified individual (QI) - Full style:	ECM Maritime Services, LLC 1 Selleck Street, 5th Floor, Suite 511 Norwalk, CT 06855, USA. Tel: +1.203.857.0444 Fax: +1.203.857.0428 Email: ecm@ecmmaritime.com Web: www.ecmmaritime.com	
5.3	Oil Spill Response Organization (OSRO) -Full style:	NATIONAL RESPONSE CORPORATION 3500 Sunrise hwy Ste. T103 Great river, NY 11739, USA. Tel: +1.800.899.4672 Fax: +1.631.224.9086 Email: iocdo@nrcc.com	
5.4	Has technical operator signed the SCIA / C-TPAT agreement with US customs concerning drug smuggling:	No	

<b>6.</b>	<b>CARGO AND BALLAST HANDLING</b>		
<b>Double Hull Vessels</b>			
6.1	Is vessel fitted with centerline bulkhead in all cargo tanks:	Yes	
6.2	If Yes, is bulkhead solid or perforated:	SOLID SS 316 L	
<b>Cargo Tank Capacities</b>			
6.3	Capacity (98%) of each natural segregation with double valve (specify tanks):	Seg#1: 1957.669 (1P) Seg#2: 1959.312 (1S) Seg#3: 2316.128 (2P) Seg#4: 2326.365 (2S) Seg#5: 2392.382 (3P) Seg#6: 2402.479 (3S) Seg#7: 2391.335 (4P) Seg#8: 2403.168 (4S) Seg#9: 2391.665 (5P) Seg#10: 2404.301 (5S) Seg#11: 2391.703 (6P)	

**INTERTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 (Q88)**

		Seg#12: 2402.006 (6S) Seg#13: 2358.526 (7P) Seg#14: 2369.143 (7S) Seg#15: 2169.638 (8P) Seg#16: 2180.626 (8S) Slop: 755.810 (Slop P) Slop: 755.506 (Slop S)		
6.4	Total cubic capacity (98%, excluding slop tanks):	36816.452 Cu. Metres		
6.5	Slop tank(s) capacity (98%):	1511.316 Cu. Metres		
6.6	Residual/Retention oil tank(s) capacity (98%), if applicable:	56.07 Cu meters		
6.7	Does vessel have Segregated Ballast Tanks (SBT) or Clean Ballast Tanks (CBT):	SBT		
<b>SBT Vessels</b>				
6.8	What is total capacity of SBT?	12739.63 Cu. Metres		
6.9	What percentage of SDWT can vessel maintain with SBT only:	36.2 %		
6.10	Does vessel meet the requirements of MARPOL Annex I Reg 18.2: (previously Reg 13.2)	Yes		
<b>Cargo Handling</b>				
6.11	How many grades/products can vessel load/discharge with double valve segregation:	18		
6.12	Maximum loading rate for homogenous cargo per manifold connection:	408.6 Cu. Metres/Hour		
6.13	Maximum loading rate for homogenous cargo loaded simultaneously through all manifolds:	3268.8 Cu. Metres/Hour		
6.14	Are there any cargo tank filling restrictions. If yes, please specify:	Yes $\rho=1.30$ (Sloshing 1.85)		
<b>Pumping Systems</b>				
6.15	Pumps:	No.	Type	Capacity
	Cargo:	16/ 2	Framo	300 / 200 Cu M/Hr
	Stripping:			
	Eductors:			
	Ballast:	2	Framo	650 Cu M/hr
6.16	How many cargo pumps can be run simultaneously at full capacity:	5		
<b>Cargo Control Room</b>				
6.17	Is ship fitted with a Cargo Control Room (CCR):	Yes		
6.18	Can tank innage / ullage be read from the CCR:	Yes		
<b>Gauging and Sampling</b>				
6.19	Can ship operate under closed conditions in accordance with ISGOTT:	Yes		
6.20	What type of fixed closed tank gauging system is fitted:	RADAR TYPE ( level echo ) & Float type for 2 Slop Tanks		
6.21	Are overfill (high-high) alarms fitted? If Yes, indicate whether to all tanks or partial:	YES, ALL TANKS		
<b>Vapor Emission Control</b>				
6.22	Is a vapor return system (VRS) fitted:	Yes		
6.23	Number/size of VRS manifolds (per side):	2	200 Millimetres	
<b>Venting</b>				
6.24	State what type of venting system is fitted:	High Velocity PV ( Press Vac )		
<b>Cargo Manifolds</b>				
6.25	Does vessel comply with the latest edition of the OCIMF 'Recommendations for Oil Tanker Manifolds and Associated Equipment':	YES		
6.26	What is the number of cargo connections per side:	18		
6.27	What is the size of cargo connections:	150 Millimetres		
6.28	What is the material of the manifold:	SUS 316L		
<b>Manifold Arrangement</b>				
6.29	Distance between cargo manifold centers:	500 Millimetres		
6.30	Distance ships rail to manifold:	3407 Millimetres		
6.31	Distance manifold to ships side:	3550 Millimetres		

**INTERTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 (Q88)**

6.32	Top of rail to center of manifold:	1829 Millimetres	
6.33	Distance main deck to center of manifold:	3108 Millimetres	
6.34	Manifold height above the waterline in normal ballast / at SDWT condition:	13.07Meters	7.82 Meters
6.35	Number / size reducers:	2 / 200mm – 200mm / 8" 2 / 250mm /10" -> JIS 100A (100mm )4" 2 / 200mm /8" ->150mm /6" 2 / 150mm /6"->100mm / 4" 1 / 300mm / 12"-> 250mm / 10" 2 / 250mm /10"-> 200mm / 8" 2 / 250mm /10"-> 150mm / 6" 2 / 200mm / 8" -> 150mm/ 6" 4 / 150mm / 6" -> 100mm / 4"	

**Stern Manifold**

6.36	Is vessel fitted with a stern manifold:	No
6.37	If stern manifold fitted, state size:	NA

**Cargo Heating**

6.38	Type of cargo heating system?	Steam	
6.39	If fitted, are all tanks coiled?	Yes	
6.40	If fitted, what is the material of the heating coils:	SS316 L	
6.41	Maximum temperature cargo can be loaded/maintained:	90 C	75 C

**Tank Coating**

6.42	Are cargo, ballast and slop tanks coated?	Coated	Type	To What Extent
	Cargo tanks:	YES	Stainless Steel (SUS 316LN) & SUS Clad Steel(SUS316L)	Whole Tank
	Ballast tanks:	Yes	NTE HB x 2 (applied to PSPC)	Whole Tank
	Slop tanks:	Yes	Stainless Steel (SUS 316LN) & SUS Clad Steel(SUS316L)	Whole Tank
6.43	If fitted, what type of anodes are used:	NA		

**7. INERT GAS AND CRUDE OIL WASHING**

7.1	Is an Inert Gas System (IGS) fitted:	YES 1875Nm3/Hr @ 95.0% N2 1300Nm3/Hr @ 95.0% N2 930Nm3/Hr @ 95.0% N2 560Nm3/Hr @ 95.0% N2 375Nm3/Hr @ 95.0% N2
7.2	Is IGS supplied by flue gas, inert gas (IG) generator and/or nitrogen:	NITROGEN GENERATOR
7.3	Is a Crude Oil Washing (COW) installation fitted:	N/A

**8. MOORING**

8.1	Mooring wires (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	N/A	N/A	N/A	N/A	N/A
	Main deck fwd:	N/A	N/A	N/A	N/A	N/A
	Main deck aft:	N/A	N/A	N/A	N/A	N/A
	Poop deck:	N/A	N/A	N/A	N/A	N/A
8.2	Wire tails	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	N/A	N/A	N/A	N/A	N/A
	Main deck fwd:	N/A	N/A	N/A	N/A	N/A
	Main deck aft:	N/A	N/A	N/A	N/A	N/A
	Poop deck:	N/A	N/A	N/A	N/A	N/A
8.3	Mooring ropes (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	6	60 Millimetres	Polypropylene and Polyester Composite	220 Metres	53.2 Metric Tonnes

**INTERTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 (Q88)**

	Main deck fwd:	N/A				
	Main deck aft:	N/A				
	Poop deck:	6	60 Millimetres	Polypropylene and Polyester Composite	220 Metres	53.2 Metric Tonnes
8.4	Other mooring lines	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	5	60 Millimetres	Polypropylene and Polyester Composite	200 Metres	53.2 Metric Tonnes
	Main deck fwd:	N/A	N/A	N/A	N/A	N/A
	Main deck aft:	N/A	N/A	N/A	N/A	N/A
	Poop deck:	5	60 Millimetres	Polypropylene and Polyester Composite	200 Metres	53.2 Metric Tonnes
8.5	Mooring winches			No.	# Drums	Brake Capacity
			Forecastle:	3	6	31.93 Tonnes
			Main deck fwd:	N/A		
			Main deck aft:	N/A		
			Poop deck:	2	6	31.93 Tonnes
8.6	Mooring bitts				No.	SWL
			Forecastle:	1		111 Metric Tonnes
				3		64 Metric Tonnes
			Main deck fwd:	2		64 Metric Tonnes
				2		52 Metric Tonnes
			Main deck aft:	2		64 Metric Tonnes
				2		52 Metric Tonnes
			Poop deck:	1		111 Metric Tonnes
				3		64 Metric Tonnes
				4		52 Metric Tonnes
8.7	Closed chocks and/or fairleads of enclosed type				No.	SWL
			Forecastle:	1		204 Metric Tonnes
				2		126 Metric Tonnes
			Main deck fwd:	2		89 Metric Tonnes
				12		80 Metric Tonnes
			Main deck aft:	2		80 Metric Tonnes
			Poop deck:	3		126 Metric Tonnes
				2		89 Metric Tonnes
<b>Emergency Towing System</b>						
8.8	Type / SWL of Emergency Towing system forward:				ETS4000FSR-SJ	204 Metric Tonnes
8.9	Type / SWL of Emergency Towing system aft:				ETS2000A-SJ	102 Metric Tonnes
<b>Anchors</b>						
8.10	Number of shackles on port cable:					11
8.11	Number of shackles on starboard cable:					11
<b>Escort Tug</b>						
8.12	What is SWL and size of closed chock and/or fairleads of enclosed type on stern:				126 Metric Tonnes	250x450mm
8.13	What is SWL of bollard on poopdeck suitable for escort tug:					111 Metric Tonnes
<b>Bow/Stern Thruster</b>						
8.14	What is brake horse power of bow thruster (if fitted):				NA	
8.15	What is brake horse power of stern thruster (if fitted):				NA	
<b>Single Point Mooring (SPM) Equipment</b>						
8.16	Does vessel comply with the latest edition of OCIMF 'Recommendations for Equipment Employed in the Mooring of Vessels at Single Point Moorings (SPM)':					YES
8.17	Is vessel fitted with chain stopper(s):					YES
8.18	How many chain stopper(s) are fitted:				1	
8.19	State type of chain stopper(s) fitted:				TONGUE TYPE	

**INTERTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 (Q88)**

8.20	Safe Working Load (SWL) of chain stopper(s):	204 Metric Tonnes
8.21	What is the maximum size chain diameter the bow stopper(s) can handle:	φ76
8.22	Distance between the bow fairlead and chain stopper/bracket:	3,202 Millimetres
8.23	Is bow chock and/or fairlead of enclosed type of OCIMF recommended size (600mm x 450mm)? If not, give details of size:	Yes
<b>Lifting Equipment</b>		
8.24	Derrick / Crane description (Number, SWL and location):	Cranes: 1 x 10 Tonnes, Midship
8.25	What is maximum outreach of cranes / derricks outboard of the ship's side:	4.3 Metres
<b>Ship To Ship Transfer (STS)</b>		
8.26	Does vessel comply with recommendations contained in OCIMF/ICS Ship To Ship Transfer Guide (Petroleum or Liquefied Gas, as applicable):	YES

<b>9.</b>	<b>MISCELLANEOUS</b>	
<b>Engine Room</b>		
9.1	What type of fuel is used for main propulsion?	HFO 380 CST
9.2	What type of fuel is used in the generating plant?	HFO & MGO
9.3	Capacity of bunker tanks - IFO and MDO/MGO:	1574.81 Cu. Metres      203.26 Cu. Metres 0 Cu. Metres
9.4	Is vessel fitted with fixed or controllable pitch propeller(s)?	Fixed
<b>Insurance</b>		
9.5	P & I Club - Full Style:	Assuranceforeningen Skuld (Gjensidig) Skuld Singapore Branch office #37-01,6 Battery Road 049909,SINGAPORE Emergency :+ 47 952 92200 Tel: +65 6438 8010 Fax : +65 6438 0180 Email:sng@skuld.com
9.6	P & I Club coverage - pollution liability coverage:	1,000,000,000 US\$
<b>Port State Control</b>		
9.7	Date and place of last Port State Control inspection:	N/A
9.8	Any outstanding deficiencies as reported by any Port State Control:	N/A
9.9	If yes, provide details:	
<b>Recent Operational History</b>		
9.10	Has vessel been involved in a pollution, grounding, serious casualty or collision incident during the past 12 months? If yes, full description:	N/A
9.11	Last three cargoes / charterers / voyages (Last / 2nd Last / 3rd Last):	Private and Confidential as per Charter Party. Please contact owner for detail.
<b>Vetting</b>		
9.12	Date/Place of last SIRE Inspection:	N/A
9.13	Date/Place of last CDI Inspection:	N/A
9.14	Recent Oil company inspections/screenings (To the best of owners knowledge and without guarantee of acceptance for future business)*:  * "Approvals" are not given by Oil Majors and ships are accepted for the voyage on a case by case basis.	

Version 3 ([www.Intertanko.com](http://www.Intertanko.com) / [www.Q88.com](http://www.Q88.com))

Form completed on <http://www.q88.com/integration.aspx> Please email [support@q88.com](mailto:support@q88.com) an updated copy if this is not the latest version.

To the best of owners knowledge all information is true and given without any guarantee