

<b>1.</b>	<b>VESSEL DESCRIPTION</b>		
1.1	Date updated:	May 31, 2017	
1.2	Vessel's name:	MTM Fairfield	
1.3	IMO number:	9264465	
1.4	Vessel's previous name(s) and date(s) of change:	CHEMSTAR HERO (Jun 15, 2009)	
1.5	Date delivered:	Sep 10, 2002	
1.6	Builder (where built):	FUKUOKA SHIPBUILDING CO. LTD	
1.7	Flag:	Singapore	
1.8	Port of Registry:	Singapore	
1.9	Call sign:	9V9680	
1.10	Vessel's satcom phone number:	+ 8816777 35797 /+ 1 201 2447576 /+ 65 3158 2947 / 456 629 210	
	Vessel's fax number:	NA	
	Vessel's telex number:	NA	
	Vessel's email address:	master.mtf@mtmship.com; master.mtmfairfield@mtmsm.amosconnect.com	
1.11	Type of vessel:	Oil/Chemical Tanker	
1.12	Type of hull:	Double Hull	
<b>Classification</b>			
1.13	Classification society:	Nippon Kaiji Kyokai	
1.14	Class notation:	NS*(CT II and III)(ESP)/MNS*	
1.15	If Classification society changed, name of previous society:	N/A	
1.16	If Classification society changed, date of change:		
1.17	IMO type, if applicable:	2,3	
1.18	Does the vessel have ice class? If yes, state what level :	No,	
1.19	Date / place of last dry-dock:	Jul 13, 2015	Busan, S. Korea
1.20	Date next dry dock due	Sep 09, 2017	
1.21	Date of last special survey / next survey due:	Aug 13, 2012	Sep 09, 2017
1.22	Date of last annual survey:	Jun 12, 2016	
1.23	If ship has Condition Assessment Program (CAP), what is the latest overall rating:		
1.24	Does the vessel have a statement of compliance issued under the provisions of the Condition Assessment Scheme (CAS): If yes, what is the expiry date?	N/A	
<b>Dimensions</b>			
1.25	Length Over All (LOA):	144.00 Metres	
1.26	Length Between Perpendiculars (LBP):	136.00 Metres	
1.27	Extreme breadth (Beam):	24.20 Metres	
1.28	Moulded depth:	12.80 Metres	
1.29	Keel to Masthead (KTM) / KTM in collapsed condition (if applicable):	36.30 Metres	
1.30	Bow to Center Manifold (BCM) / Stern to Center Manifold (SCM):	67.70 Metres	76.30 Metres
1.31	Distance bridge front to center of manifold:	45.25 Metres	
1.32	Parallel body distances:	Lightship	Normal Ballast
	Forward to mid-point manifold:	23.60 Metres	30.75 Metres
	Aft to mid-point manifold:	23.55 Metres	29.35 Metres
	Parallel body length:	47.15 Metres	60.10 Metres
1.33	FWA at summer draft / TPC immersion at summer draft:	212 Millimetres	29.85 Metric Tonnes
1.34	What is the max height of mast above waterline (air draft)	Full Mast	Collapsed Mast
	Lightship:	34.002 Metres	0 Metres
	Normal ballast:	29.395 Metres	0 Metres
	At loaded summer deadweight:	26.483 Metres	0 Metres
<b>Tonnages</b>			
1.35	Net Tonnage:	6,366	
1.36	Gross Tonnage / Reduced Gross Tonnage (if applicable):	11,552	9,488

**INTERTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 (Q88)**

1.37	Suez Canal Tonnage - Gross (SCGT) / Net (SCNT):		12,065.68	10,435.55	
1.38	Panama Canal Net (PCNT):			9,722	
<b>Loadline Information</b>					
1.39	Loadline Annex I	Freeboard	Draft	Deadweight	Displacement
	Summer:	3.211 Metres	9.62 Metres	19,996.72 Metric Tonnes	25,282.01 Metric Tonnes
	Winter:	3.411 Metres	9.42 Metres	19,402.29 Metric Tonnes	24,687.58 Metric Tonnes
	Tropical:	3.011 Metres	9.82 Metres	20,594.23 Metric Tonnes	25,879.52 Metric Tonnes
	Lightship:	10.533 Metres	2.298 Metres		5,285.29 Metric Tonnes
	Normal Ballast Condition:	7.122 Metres	5.709 Metres	8,903 Metric Tonnes	14,187.978 Metric Tonnes
1.39	Loadline Annex II	Freeboard	Draft	Deadweight	Displacement
	Summer:	3.014 Metres	9.817 Metres	20,585 Metric Tonnes	25,870.535 Metric Tonnes
	Winter:	3.218 Metres	9.613 Metres	19,975.86 Metric Tonnes	25,261.15 Metric Tonnes
	Tropical:	3.014 Metres	9.817 Metres	20,585.245 Metric Tonnes	25,870.535 Metric Tonnes
	Lightship:	10.533 Metres	2.298 Metres		5,285.29 Metric Tonnes
	Normal Ballast Condition:	7.122 Metres	5.709 Metres	8,903 Metric Tonnes	14,187.978 Metric Tonnes
1.40	Does vessel have multiple SDWT?				Yes
1.41	If yes, what is the maximum assigned deadweight?				20,585.25 Metric Tonnes
<b>Ownership and Operation</b>					
1.42	Registered owner - Full style:				MTM FAIRFIELD PTE. LTD. C/O, M.T.M. Ship Management Pte Ltd, 78 Shenton Way, #13-01 Singapore 079120 Tel: +65 6221 2255 Fax: +65 6221 2277 Email: marine@mtmsm.com Company IMO#: 5635491
1.43	Technical operator - Full style:				M.T.M Ship Management Pte Ltd. 78 Shenton Way, #13-01, Singapore 079120 Tel: +65-6304 1770 Fax: +65-6220 7988 Email: marine@mtmsm.com Web: www.mtmshipmanagement.com Company IMO#: 1314037
1.44	Commercial operator - Full style:				M.T. Maritime Management (USA) LLC 2960 Post Road   Southport, CT 06890, USA Tel: +1 203 226-7882 Fax: +1 203 226-8934 Telex: Not Applicable Email: operations@mtmaritime.com Web: www.mtmaritime.com
1.45	Disponent owner - Full style:				MTM Trading LLC Trust Company Complex, Ajeltake Island, Ajeltake Road, Majuro, Marshall Islands MH 96960

2.	CERTIFICATION	Issued	Last Annual or Intermediate	Expires
2.1	Safety Equipment Certificate:	Sep 25, 2015		Sep 09, 2017
2.2	Safety Radio Certificate:	Sep 10, 2012	Jun 12, 2016	Sep 09, 2017
2.3	Safety Construction Certificate:	Oct 10, 2013	Jun 12, 2016	Sep 09, 2017
2.4	Load line Certificate:	Sep 10, 2012	Jun 12, 2016	Sep 09, 2017

**INTERTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 (Q88)**

2.5	International Oil Pollution Prevention Certificate (IOPPC):	Oct 17, 2016		Sep 09, 2017
2.6	Safety Management Certificate (SMC):	Dec 29, 2016		Nov 12, 2021
2.7	Document of Compliance (DOC):	Sep 02, 2016		Sep 16, 2021
2.8	USCG (specify: COC, LOC or COI): COC	Aug 18, 2014		Aug 18, 2016
2.9	Civil Liability Convention Certificate (CLC):	Jan 05, 2017		Feb 20, 2018
2.10	Civil Liability for Bunker Oil Pollution Damage Convention Certificate (CLBC):	Jan 05, 2017		Feb 20, 2018
2.11	U.S. Certificate of Financial Responsibility (COFR):	Jun 17, 2015		Jun 17, 2018
2.12	Certificate of Fitness (Chemicals):	May 09, 2014	Jun 12, 2016	Sep 09, 2017
2.13	Certificate of Fitness (Gas):	Not Applicable	Not Applicable	Not Applicable
2.14	Certificate of Class:	Sep 10, 2012	Jun 12, 2016	Sep 09, 2017
2.15	International Ship Security Certificate (ISSC):	Oct 21, 2016		Nov 12, 2021
2.16	International Sewage Pollution Prevention Certificate (ISPPC)	Sep 10, 2012		Sep 09, 2017
2.17	International Air Pollution Prevention Certificate (IAPP):	Sep 10, 2012	Jun 12, 2016	Sep 09, 2017

**Documentation**

2.18	Does vessel have all updated publications as listed in the Vessel Inspection Questionnaire, Chapter 2- Question 2.24, as applicable:	Yes
2.19	Owner warrant that vessel is member of ITOPF and will remain so for the entire duration of this voyage/contract:	Yes

<b>3.</b>	<b>CREW MANAGEMENT</b>		
3.1	Nationality of Master:	Burmese	
3.2	Nationality of Officers:	Burmese	
3.3	Nationality of Crew:	Burmese	
3.4	If Officers/Crew employed by a Manning Agency - Full style:	Officers: N/A, Directly employed by Technical Operator Crew: N/A, directly employed by Technical Operator	
3.5	What is the common working language onboard:	ENGLISH	
3.6	Do officers speak and understand English:	Yes	
3.7	In case of Flag Of Convenience, is the ITF Special Agreement on board:	N/A	

<b>4.</b>	<b>HELICOPTERS</b>		
4.1	Can the ship comply with the ICS Helicopter Guidelines:	No	
4.2	If Yes, state whether winching or landing area provided:		

<b>5.</b>	<b>FOR USA CALLS</b>		
5.1	Has the vessel Operator submitted a Vessel Spill Response Plan to the US Coast Guard which has been approved by official USCG letter:	Yes	
5.2	Qualified individual (QI) - Full style:	ECM Maritime Services, LLC 1 Selleck Street, 5th Floor, Suite 511 Norwalk, CT 06855, USA. Tel: +1.203.857.0444 Fax: +1.203.857.0428 Email: ecm@ecmmaritime.com Web: www.ecmmaritime.com	
5.3	Oil Spill Response Organization (OSRO) -Full style:	NATIONAL RESPONSE CORPORATION 3500 Sunrise hwy Ste. T103 Great river, NY 11739, USA. Tel: +1.800.899.4672 Fax: +1.631.224.9086 Email: iocdo@nrcc.com	
5.4	Has technical operator signed the SCIA / C-TPAT agreement with US customs concerning drug smuggling:	No	

<b>6.</b>	<b>CARGO AND BALLAST HANDLING</b>		
<b>Double Hull Vessels</b>			

**INTERTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 (Q88)**

6.1	Is vessel fitted with centerline bulkhead in all cargo tanks:	Yes
6.2	If Yes, is bulkhead solid or perforated:	Solid
<b>Cargo Tank Capacities</b>		
6.3	Capacity (98%) of each natural segregation with double valve (specify tanks):	Seg#1: 620.094(1P) Seg#2: 633.019 (1S) Seg#3: 516.623 (2P) Seg#4: 529.087 (2S) Seg#5: 1494.604 (3P) Seg#6: 1495.864 (3S) Seg#7: 730.279 (4P) Seg#8: 745.109 (4S) Seg#9: 1391.570 (5P) Seg#10: 1404.415(5S) Seg#11: 731.015 (6P) Seg#12: 745.605 (6S) Seg#13: 1314.026 (7P) Seg#14: 1313.967 (7S) Seg#15: 1391.320 (8P) Seg#16: 1404.754 (8S) Seg#17: 1306.612(9P) Seg#18: 1306.730 (9S) Seg#19: 690.703 (10P) Seg#20: 704.130 (10S) Slop: 523.722 (11P) Slop: 596.449 (11S) (Total 22 tanks of each natural segregation with double valve.)
6.4	Total cubic capacity (98%, excluding slop tanks):	21,649.471 Cu. Metres (Slop tanks are also cargo tanks.)
6.5	Slop tank(s) capacity (98%):	0 Cu. Metres
6.6	Residual/Retention oil tank(s) capacity (98%), if applicable:	
6.7	Does vessel have Segregated Ballast Tanks (SBT) or Clean Ballast Tanks (CBT):	SBT
<b>SBT Vessels</b>		
6.8	What is total capacity of SBT?	7,074.34 Cu. Metres
6.9	What percentage of SDWT can vessel maintain with SBT only:	35.70 %
6.10	Does vessel meet the requirements of MARPOL Annex I Reg 18.2: (previously Reg 13.2)	Yes
<b>Cargo Handling</b>		
6.11	How many grades/products can vessel load/discharge with double valve segregation:	22
6.12	Maximum loading rate for homogenous cargo per manifold connection:	476 Cu. Metres/Hour
6.13	Maximum loading rate for homogenous cargo loaded simultaneously through all manifolds:	1,904 Cu. Metres/Hour
6.14	Are there any cargo tank filling restrictions. If yes, please specify:	Yes Designed Specific Capacity 1.5 Ton/M3
<b>Pumping Systems</b>		
6.15	Pumps:	No. Type Capacity
	Cargo:	22 Centrifugal 200 M3/HR
	Stripping:	
	Eductors:	
	Ballast:	1 Centrifugal 400 Cu. Metres/Hour
6.16	How many cargo pumps can be run simultaneously at full capacity:	4
<b>Cargo Control Room</b>		
6.17	Is ship fitted with a Cargo Control Room (CCR):	Yes
6.18	Can tank innage / ullage be read from the CCR:	Yes
<b>Gauging and Sampling</b>		
6.19	Can ship operate under closed conditions in accordance with ISGOTT:	Yes
6.20	What type of fixed closed tank gauging system is fitted:	Floating
6.21	Are overfill (high-high) alarms fitted? If Yes, indicate whether to all tanks or partial:	All tanks
<b>Vapor Emission Control</b>		

**INTERTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 (Q88)**

6.22	Is a vapor return system (VRS) fitted:	Yes	
6.23	Number/size of VRS manifolds (per side):	1	150 Millimetres

**Venting**

6.24	State what type of venting system is fitted:	Individual	
------	--	------------	--

**Cargo Manifolds**

6.25	Does vessel comply with the latest edition of the OCIMF 'Recommendations for Oil Tanker Manifolds and Associated Equipment':	N/A	
6.26	What is the number of cargo connections per side:	22	
6.27	What is the size of cargo connections:	150 Millimetres	
6.28	What is the material of the manifold:	SUS 316L	

**Manifold Arrangement**

6.29	Distance between cargo manifold centers:	400 Millimetres	
6.30	Distance ships rail to manifold:	4,200 Millimetres	
6.31	Distance manifold to ships side:	4,250 Millimetres	
6.32	Top of rail to center of manifold:	1,107 Millimetres	
6.33	Distance main deck to center of manifold:	2,600 Millimetres	
6.34	Manifold height above the waterline in normal ballast / at SDWT condition:	9.722 Metres	6.20 Metres
6.35	Number / size reducers:	4 x 150/100mm (6/4") 2 x 150/150mm (6/6") 2 x 150/200mm (6/8") 2 x 150/250mm (6/10") 1 x 150/300mm (6/12")	

**Stern Manifold**

6.36	Is vessel fitted with a stern manifold:	No	
6.37	If stern manifold fitted, state size:		

**Cargo Heating**

6.38	Type of cargo heating system?	Steam	
6.39	If fitted, are all tanks coiled?	Yes	
6.40	If fitted, what is the material of the heating coils:	Stainless Steel	
6.41	Maximum temperature cargo can be loaded/maintained:	80.0 °C / 176.0 °F	65 °C / 149 °F

**Tank Coating**

6.42	Are cargo, ballast and slop tanks coated?	Coated	Type	To What Extent
	Cargo tanks:	No	SUS316L (SS)	
	Ballast tanks:	Yes	Epoxy	Whole Tank
	Slop tanks:	No	SUS 316L (SS)	
6.43	If fitted, what type of anodes are used:			

**7. INERT GAS AND CRUDE OIL WASHING**

7.1	Is an Inert Gas System (IGS) fitted:	No	
7.2	Is IGS supplied by flue gas, inert gas (IG) generator and/or nitrogen:	Nitrogen (Bottled)	
7.3	Is a Crude Oil Washing (COW) installation fitted:	N/A	

**8. MOORING**

8.1	Mooring wires (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	0	0 Millimetres	0	0 Metres	0 Metric Tonnes
	Main deck fwd:	0	0 Millimetres	0	0 Metres	0 Metric Tonnes
	Main deck aft:	0	0 Millimetres	0	0 Metres	0 Metric Tonnes
	Poop deck:	0	0 Millimetres	0	0 Metres	0 Metric Tonnes
8.2	Wire tails	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	0	0 Millimetres	0	0 Metres	0 Metric Tonnes
	Main deck fwd:	0	0 Millimetres	0	0 Metres	0 Metric Tonnes
	Main deck aft:	0	0 Millimetres	0	0 Metres	0 Metric Tonnes
	Poop deck:	0	0 Millimetres	0	0 Metres	0 Metric Tonnes
8.3	Mooring ropes (on drums)	No.	Diameter	Material	Length	Breaking Strength

**INTERTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 (Q88)**

	Forecastle:	4	65 Millimetres	Polypropylene & Polyester Interwoven	200 Metres	61.90 Metric Tonnes
	Main deck fwd:	0	0 Millimetres	0	0 Metres	0 Metric Tonnes
	Main deck aft:	0	0 Millimetres	0	0 Metres	0 Metric Tonnes
	Poop deck:	4	65 Millimetres	Polypropylene & Polyester Interwoven	200 Metres	61.90 Metric Tonnes
8.4	Other mooring lines	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	3	65 Millimetres	Polypropylene & Polyester Interwoven	200 Metres	61.90 Metric Tonnes
	Main deck fwd:	0	0 Millimetres	0	0 Metres	0 Metric Tonnes
	Main deck aft:	0	0 Millimetres	0	0 Metres	0 Metric Tonnes
	Poop deck:	3	65 Millimetres	Polypropylene & Polyester Interwoven	200 Metres	61.90 Metric Tonnes
8.5	Mooring winches			No.	# Drums	Brake Capacity
	Forecastle:			2	Double	31.70 Metric Tonnes
	Main deck fwd:			0		0 Metric Tonnes
	Main deck aft:			0		0 Metric Tonnes
	Poop deck:			2	Double	25.50 Metric Tonnes
8.6	Mooring bitts				No.	SWL
	Forecastle:				6	72 Metric Tonnes
	Main deck fwd:				2	57 Metric Tonnes
	Main deck aft:				2	57 Metric Tonnes
	Poop deck:				10	72 Metric Tonnes
8.7	Closed chocks and/or fairleads of enclosed type				No.	SWL
	Forecastle:				3	82 Metric Tonnes
	Main deck fwd:				2	77 Metric Tonnes
	Main deck aft:				2	77 Metric Tonnes
	Poop deck:				5	82 Metric Tonnes
<b>Emergency Towing System</b>						
8.8	Type / SWL of Emergency Towing system forward:				ETS- 4000-FSR-SJ	200 Metric Tonnes
8.9	Type / SWL of Emergency Towing system aft:				ETS- 2000A-SJ	100 Metric Tonnes
<b>Anchors</b>						
8.10	Number of shackles on port cable:					10.50
8.11	Number of shackles on starboard cable:					10.50
<b>Escort Tug</b>						
8.12	What is SWL and size of closed chock and/or fairleads of enclosed type on stern:				64 Metric Tonnes	Not Applicable
8.13	What is SWL of bollard on poopdeck suitable for escort tug:					72 Metric Tonnes
<b>Bow/Stern Thruster</b>						
8.14	What is brake horse power of bow thruster (if fitted):				0 bhp	0 Kilowatt
8.15	What is brake horse power of stern thruster (if fitted):					0 Kilowatt
<b>Single Point Mooring (SPM) Equipment</b>						
8.16	Does vessel comply with the latest edition of OCIMF 'Recommendations for Equipment Employed in the Mooring of Vessels at Single Point Moorings (SPM)':					No
8.17	Is vessel fitted with chain stopper(s):					No
8.18	How many chain stopper(s) are fitted:				0	
8.19	State type of chain stopper(s) fitted:				0	
8.20	Safe Working Load (SWL) of chain stopper(s):					0 Metric Tonnes
8.21	What is the maximum size chain diameter the bow stopper(s) can handle:					0 Millimetres
8.22	Distance between the bow fairlead and chain stopper/bracket:					0 Millimetres
8.23	Is bow chock and/or fairlead of enclosed type of OCIMF recommended size (600mm x 450mm)? If not, give details of size:					Yes
<b>Lifting Equipment</b>						
8.24	Derrick / Crane description (Number, SWL and location):					Cranes: 1 x 5 Tonnes, Midship
8.25	What is maximum outreach of cranes / derricks outboard of the ship's side:					5 Metres

**INTERTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 (Q88)**

Ship To Ship Transfer (STS)		
8.26	Does vessel comply with recommendations contained in OCIMF/ICS Ship To Ship Transfer Guide (Petroleum or Liquefied Gas, as applicable):	No

**9. MISCELLANEOUS**

Engine Room			
9.1	What type of fuel is used for main propulsion?	IFO 380CST	
9.2	What type of fuel is used in the generating plant?	IFO 380 CST	
9.3	Capacity of bunker tanks - IFO and MDO/MGO:	1,088.46 Cu. Metres	121.36 Cu. Metres 0 Cu. Metres
9.4	Is vessel fitted with fixed or controllable pitch propeller(s)?	Fixed Pitch	

**Insurance**

9.5	P & I Club - Full Style:	NORTH OF ENGLAND The Quayside, Newcastle upon Tyne, NE13DU UK Tel: +44(0)191 2325 221 Fax: +44 (0) 191 2610 540 Email: general@nepia.com Web: www.nepia.com	
9.6	P & I Club coverage - pollution liability coverage:	1,000,000,000 US\$	

**Port State Control**

9.7	Date and place of last Port State Control inspection:	May 13, 2017 / Rotterdam
9.8	Any outstanding deficiencies as reported by any Port State Control:	No
9.9	If yes, provide details:	

**Recent Operational History**

9.10	Has vessel been involved in a pollution, grounding, serious casualty or collision incident during the past 12 months? If yes, full description:	Pollution: No, Grounding: No , Serious casualty: No , Collision: No ,	
9.11	Last three cargoes / charterers / voyages (Last / 2nd Last / 3rd Last):	Private and Confidential as per Charter Party. Please contact owner for detail.	

**Vetting**

9.12	Date/Place of last SIRE Inspection:	Dec 24, 2016 / VUNG TAO	
9.13	Date/Place of last CDI Inspection:	Jun 01, 2016 / Ulsan	
9.14	Recent Oil company inspections/screenings (To the best of owners knowledge and without guarantee of acceptance for future business)*:  * "Approvals" are not given by Oil Majors and ships are accepted for the voyage on a case by case basis.	Tesoro/ IDEMITSU / PHILIPS66 / CDI	

 Version 3 ([www.Intertanko.com](http://www.Intertanko.com) / [www.Q88.com](http://www.Q88.com))

 Form completed on <http://www.q88.com/integration.aspx> Please email [support@q88.com](mailto:support@q88.com) an updated copy if this is not the latest version.

To the best of owners knowledge all information is true and given without any guarantee