er		

1.	VESSEL DESCRIPTION	TIONNAINE 00 (Q00)		Version 3
1.1	Date updated:		May 3 <sup>2</sup>	1, 2017
1.2	Vessel's name:		MTM Yangon	
1.3	IMO number:		9250165	
1.4	Vessel's previous name(s) and date(s) of change:		Sinbad (Apr 21, 2013)	
1.5	Date delivered:		Aug 29	9, 2003
1.6	Builder (where built):		Hyundai Mipo, Ulsan,	
1.7	Flag:		Singapore	
1.8	Port of Registry:		Singapore	
1.9	Call sign:		9V2087	
1.10	Vessel's satcom phone number:		+870 773 156 163	
	Vessel's fax number:		+870 765 110 012	
	Vessel's telex number:		456 691 410/ 456 691	411
	Vessel's email address:		master.yangon@mtms	
1.11	Type of vessel:			ical Tanker
1.12	Type of hull:			le Hull
	ification		Double	10 11411
1.13	Classification society:		American Bureau of S	hinning
1.14	Class notation:		ABS+A1, Chemical Ca	
1.14	Class Hotation.		ESP, +AMS, + ACCU,	
1.15	If Classification society changed, name of previous society	ety:	N	IA
1.16	If Classification society changed, date of change:		N	IA
1.17	IMO type, if applicable:		;	3
1.18	Does the vessel have ice class? If yes, state what level:		No,	N/A
1.19	Date / place of last dry-dock:		Mar 01, 2016	Shanhaiguan, China
1.20	Date next dry dock due		Mar 03	3, 2018
1.21	Date of last special survey / next survey due:		Mar 04, 2013	Mar 03, 2018
1.22	Date of last annual survey:		Mar 29	9, 2017
1.23	If ship has Condition Assessment Program (CAP), what rating:	is the latest overall	N	/A
1.24	Does the vessel have a statement of compliance issued of the Condition Assessment Scheme (CAS): If yes, what		N/A Not Applicable	
Dime	nsions			
1.25	Length Over All (LOA):			183.024 Metres
1.26	Length Between Perpendiculars (LBP):			174 Metres
1.27	Extreme breadth (Beam):			32.23 Metres
1.28	Moulded depth:			18.80 Metres
1.29	Keel to Masthead (KTM) / KTM in collapsed condition (if	applicable):	46.50 Metres	N/
1.30	Bow to Center Manifold (BCM) / Stern to Center Manifold		90 Metres	93 Metres
1.31	Distance bridge front to center of manifold:			59.55 Metres
1.32	Parallel body distances:	Lightship	Normal Ballast	Summer Dwt
	Forward to mid-point manifold:	21.23 Metres	39.20 Metres	44.24 Metres
	Aft to mid-point manifold:	36.80 Metres	41.56 Metres	47.39 Metres
	Parallel body length:	57.93 Metres	80.76 Metres	91.63 Metres
1.33	FWA at summer draft / TPC immersion at summer draft:		269 Millimetres	52.267 Metric Tonnes
1.34	What is the max height of mast above waterline (air draf	t)	Full Mast	Collapsed Mast
	Lightship:		44.12 Metres	•
	Normal ballast:		39.24 Metres	0 Metre
	At loaded summer deadweight:		34.30 Metres	0 Metres
Tonna	· · · · · · · · · · · · · · · · · · ·			1
1.35	Net Tonnage:		11,943	
1.36	Gross Tonnage / Reduced Gross Tonnage (if applicable	e):	29,220	21,829
1.37	Suez Canal Tonnage - Gross (SCGT) / Net (SCNT):	•	30,509.27	26,222.13
	1		23,000.21	

Q88.com Page 1/7

1.38	Panama Canal Net Tonnage (PCNT):				24,2
_oad	line Information				
.39	Loadline	Freeboard	Draft	Deadweight	Displacement
	Summer:	6.612 Metres	12.20 Metres	46,818 Metric Tonnes	56,239.10 Metric Tonnes
	Winter:	6.866 Metres	11.946 Metres	45,408.10 Metric Tonnes	54,829.20 Metric Tonnes
	Tropical:	6.358 Metres	12.454 Metres	48,065.70 Metric Tonnes	57,477.80 Metric Tonnes
	Lightship:	16.448 Metres	2.38 Metres		9,421.10 Metric Tonnes
	Normal Ballast Condition:	11.568 Metres	7.26 Metres	22,175.30 Metric Tonnes	31,596.40 Metric Tonnes
.40	Does vessel have multiple SD	WT?		Yes	
.41	If yes, what is the maximum a	ssigned deadweight?		46,818 Metric Tonnes	
Owne	ership and Operation				
				78 Shenton Way, #13-01, Singapore 079120 Tel: +65 6221 2255 Fax: +65 6221 2277 Email: operations@mtmm.sg Company IMO#: 5729047	
.43	Technical operator - Full style:			MTM SHIP MANAGEI 78 SHENTON WAY, # 079120 Tel: +65 6304 1770 Fax: +65 6220 7988 Email: marine@mtmsi Web: www.mtmshipm Company IMO#: 1314	#13-01 SINGAPORE  m.com anagement.com 037
1.44	Commercial operator - Full style:			MT Maritime Manager 78 Shenton Way, #13- 079120 Tel: +65 6221 2255 Fax: +65 6221 2277 Email: operations@mt	-01, Singapore
1.45	Disponent owner - Full style:			MTM Tanker Trading Trust Company Comp Ajeltake Island, Ajeltal Majuro, Marshall Islan MH 96960	llex, ke Road,

2.	CERTIFICATION	Issued	Last Annual or Intermediate	Expires
2.1	Safety Equipment Certificate:	Mar 01, 2016	Mar 29, 2017	Mar 03, 2018
2.2	Safety Radio Certificate:	Mar 01, 2014	Mar 29, 2017	Mar 03, 2018
2.3	Safety Construction Certificate:	Mar 26, 2014	Mar 29, 2017	Mar 03, 2018
2.4	Loadline Certificate:	Mar 26, 2014	Mar 29, 2017	Mar 03, 2018
2.5	International Oil Pollution Prevention Certificate (IOPPC):	Mar 29, 2017	Not Applicable	Mar 29, 2022
2.6	Safety Management Certificate (SMC):	Sep 07, 2013	Apr 02, 2016	Sep 06, 2018
2.7	Document of Compliance (DOC):	Sep 02, 2016	Not Applicable	Sep 16, 2021
2.8	USCG (specify: COC, LOC or COI): COC	Dec 14, 2014	Not Applicable	Dec 14, 2016
2.9	Civil Liability Convention Certificate (CLC):	Feb 20, 2017		Feb 20, 2018
2.10	Civil Liability for Bunker Oil Pollution Damage Convention Certificate (CLBC):	Feb 20, 2017		Feb 20, 2018
2.11	U.S. Certificate of Financial Responsibility (COFR):	Apr 15, 2013		Apr 15, 2016
2.12	Certificate of Fitness (Chemicals):	Apr 25, 2014	Mar 29, 2017	Mar 03, 2018
2.13	Certificate of Fitness (Gas):	Not Applicable	Not Applicable	Not Applicable
2.14	Certificate of Class:	Apr 18, 2013	Mar 01, 2016	Mar 03, 2018

Q88.com Page 2 / 7

2.15	International Ship Security Certificate (ISSC):	Sep 07, 2013	Apr 02, 2016	Sep 06, 2018		
2.16	International Sewage Pollution Prevention Certificate (ISPPC)	Apr 18, 2013		Mar 03, 2018		
2.17	International Air Pollution Prevention Certificate (IAPP):	Mar 01, 2016	Mar 29, 2017	Mar 03, 2018		
Docui	Documentation					
2.18	Does vessel have all updated publications as listed in the Vessel Inspection Questionnaire, Chapter 2- Question 2.24, as applicable:		Ye	es		
2.19	Owner warrant that vessel is member of ITOPF and will remain so for the entire duration of this voyage/contract:		Ye	es		

3.	CREW MANAGEMENT	
3.1	Nationality of Master:	Indian
3.2	Nationality of Officers:	Indian, Sri Lankan
3.3	Nationality of Crew:	Indian
3.4	If Officers/Crew employed by a Manning Agency - Full style:	Officers/ Crew : Directly employed by Technical Operator
3.5	What is the common working language onboard:	English
3.6	Do officers speak and understand English:	Yes
3.7	In case of Flag Of Convenience, is the ITF Special Agreement on board:	Yes

4.	HELICOPTERS	
4.1	Can the ship comply with the ICS Helicopter Guidelines:	Yes
4.2	If Yes, state whether winching or landing area provided:	Winching

5.	FOR USA CALLS	
5.1	Has the vessel Operator submitted a Vessel Spill Response Plan to the US Coast Guard which has been approved by official USCG letter:	Yes
5.2	Qualified individual (QI) - Full style:	ECM Maritime Services ECM maritime Services, LLC 1 Selleck Street 5th Floor - Suite 511 Norwalk, CT 06855 USA Tel: +1 203 857 0444 or + Fax: +1 203 857 0428 Email: ecm@ecmmaritime.com
5.3	Oil Spill Response Organization (OSRO) -Full style:	National Response corporation Tel: +1 631 224 9141 Fax: +1 631 224 9082
5.4	Has technical operator signed the SCIA / C-TPAT agreement with US customs concerning drug smuggling:	No

6.	CARGO AND BALLAST HANDLING	
Doub	le Hull Vessels	
6.1	Is vessel fitted with centerline bulkhead in all cargo tanks:	Yes
6.2	If Yes, is bulkhead solid or perforated:	Solid
Cargo	o Tank Capacities	
6.3	Capacity (98%) of each natural segregation with double valve (specify tanks):	Seg#1: 6356.8 m3 (1PS) Seg#2: 9143.2 m3 (2PS) Seg#3: 9354.6 m3 (3PS) Seg#4: 9354.6 m3 (4PS) Seg#5: 9339.4 m3 (5PS) Seg#6: 8066.2 m3 (6PS) Seg#7: 1221.472 m3 (Slop PS)
6.4	Total cubic capacity (98%, excluding slop tanks):	51,614.80 Cu. Metres
6.5	Slop tank(s) capacity (98%):	1221.472 Cu. Metres
6.6	Residual/Retention oil tank(s) capacity (98%), if applicable:	78.40 Cu. Metres
6.7	Does vessel have Segregated Ballast Tanks (SBT) or Clean Ballast Tanks (CBT):	SBT

Q88.com Page 3 / 7

	RTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 Vessels	s (Q88)	<u> </u>	
6.8	What is total capacity of SBT?			24,781.90 Cu. Metres
6.9	What percentage of SDWT can vessel maintain with SBT only:		54.25 %	
6.10	Does vessel meet the requirements of MARPOL Annex I Reg 18.2: (previously Reg 13.2)		Yes	
Cargo	b Handling			
6.11	How many grades/products can vessel load/discharge with double valve	e	6	
0	segregation:			
6.12	Maximum loading rate for homogenous cargo per manifold connection:		· ·	7.60 Cu. Metres/Hour
6.13	Maximum loading rate for homogenous cargo loaded simultaneously the all manifolds:	rough	,	2.80 Cu. Metres/Hour
6.14	Are there any cargo tank filling restrictions. If yes, please specify:		All cargo tanks can b level filling of cargo ex up to 1.025, specific gra partial (max-66%) loade slop ta	e filled full and any cept specific gravity avity 1.54 cargo to be ed in cargo tanks and
Pump	ping Systems			
6.15	Pumps:	No.	Туре	Capacity
	Cargo:	12 2	Centrifugal Centrifugal	600 M3/HR 150 M3/HR
	Stripping:			
	Eductors:			
	Ballast:	2	Centrifugal	1,000 Cu. Metres/Hour
6.16	How many cargo pumps can be run simultaneously at full capacity:		6	
Cargo	Control Room			
6.17	Is ship fitted with a Cargo Control Room (CCR):		Yes	
6.18	Can tank innage / ullage be read from the CCR:		Yes	
Gaug	ing and Sampling			
6.19	Can ship operate under closed conditions in accordance with ISGOTT:		Yes	S
6.20	What type of fixed closed tank gauging system is fitted:		Pressure Sensor	
6.21	Are overfill (high-high) alarms fitted? If Yes, indicate whether to all tanks partial:	s or	Yes - all tanks	
Vapo	r Emission Control			
6.22	Is a vapor return system (VRS) fitted:		Yes	S
6.23	Number/size of VRS manifolds (per side):		2	300 Millimetres
Venti	ng			
6.24	State what type of venting system is fitted:		High Ve	elocity
Cargo	o Manifolds			
6.25	Does vessel comply with the latest edition of the OCIMF 'Recommendation Oil Tanker Manifolds and Associated Equipment':	tions	Yes	3
6.26	What is the number of cargo connections per side:		6	
6.27	What is the size of cargo connections:	What is the size of cargo connections:		300 Millimetres
6.28	What is the material of the manifold:		Stainless Steel	
Manif	old Arrangement			
6.29	Distance between cargo manifold centers:			2,000 Millimetres
6.30	Distance ships rail to manifold:			4,600 Millimetres
6.31	Distance manifold to ships side:			4,600 Millimetres
6.32	Top of rail to center of manifold:			850 Millimetres
6.33	Distance main deck to center of manifold:			2,100 Millimetres
6.34	Manifold height above the waterline in normal ballast / at SDWT condition	on:	13.66 Metres	8.712 Metres
6.35	Number / size reducers:		6 x 300/400mm (12/16" 12 x 300/300mm (12/12 6 x 300/250mm (12/10" 6 x 300/200mm (12/8")	2")

Q88.com Page 4/7

Stern	Manifold				
6.36	Is vessel fitted with a stern manifold:		N	lo	
6.37	If stern manifold fitted, state size:		N	IA	
Cargo	Heating		·		
6.38	Type of cargo heating system?		Heat ex	changers	
6.39	If fitted, are all tanks coiled?		No/Only S	Slop tanks	
6.40	If fitted, what is the material of the heating coils:		S	SS	
6.41	Maximum temperature cargo can be loaded/maintained:		75 °C	60 °C	
Tank	Coating		<u> </u>		
6.42	Are cargo, ballast and slop tanks coated?	Coated	Туре	To What Extent	
	Cargo tanks:	Yes	PURE EPOXY COATING	Whole Tank	
	Ballast tanks:	Yes	PURE EPOXY	Whole Tank	
	Slop tanks:	Yes	EPOXY	Whole Tank	
6.43	If fitted, what type of anodes are used:	•	Zinc(Ballast Tanks)	•	

7.	INERT GAS AND CRUDE OIL WASHING	
7.1	Is an Inert Gas System (IGS) fitted:	Yes
7.2	Is IGS supplied by flue gas, inert gas (IG) generator and/or nitrogen:	IG Generator
7.3	Is a Crude Oil Washing (COW) installation fitted:	No

8.	MOORING					
8.1	Mooring wires (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:					
	Main deck fwd:					
	Main deck aft:					
	Poop deck:					
8.2	Wire tails	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	0				
	Main deck fwd:	0				
	Main deck aft:	0				
	Poop deck:	0				
8.3	Mooring ropes (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	4	64 Millimetres	Polyester/Polyolefin Blend	220 Metres	79.40 Metric Tonnes
	Main deck fwd:	4	64 Millimetres	Polyester/Polyolefin Blend	220 Metres	79.40 Metric Tonnes
	Main deck aft:	2	64 Millimetres	Polyester/Polyolefin Blend	220 Metres	79.40 Metric Tonnes
	Poop deck:	6	64 Millimetres	Polyester/Polyolefin Blend	220 Metres	79.40 Metric Tonnes
8.4	Other mooring lines	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	5	64 Millimetres	Polyester/Polyolefin Blend	220 Metres	79.40 Metric Tonnes
	Main deck fwd:					
	Main deck aft:					
	Poop deck:	3	64 Millimetres	Polyester/Polyolefin Blend	220 Metres	79.40 Metric Tonnes
8.5	Mooring winches	•		No.	# Drums	Brake Capacity
			Forecastle:	2+2	DBL	80/64 Metric Tonnes
	Main deck fwd:			2	DBL	42 Metric Tonnes
	Main deck aft:			1	DBL	42 Metric Tonnes
	Poop deck:			2	TRPL	42 Metric Tonnes
8.6	Mooring bitts				No.	SWL
				Forecastle:	4	80 Metric Tonnes
				Main deck fwd:	4	80 Metric Tonnes
Q88.	com			•		Page 5 / 7

Q88.com Page 5 / 7

INTE	RTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 (Q88)	T	1
	Main deck aft:	2	80 Metric Tonnes
	Poop deck:	6	80 Metric Tonnes
8.7	Closed chocks and/or fairleads of enclosed type	No.	SWL
	Forecastle:	7	80 Metric Tonnes
	Main deck fwd:	12	80 Metric Tonnes
	Main deck aft:	6	80 Metric Tonnes
	Poop deck:	19	64/80 Metric Tonnes
Emer	gency Towing System		
8.8	Type / SWL of Emergency Towing system forward:	KETA 45F	200 Metric Tonnes
8.9	Type / SWL of Emergency Towing system aft:	KETA 20A	100 Metric Tonnes
Anch	ors		
8.10	Number of shackles on port cable:	12	
8.11	Number of shackles on starboard cable:	•	12
Esco	rt Tug		
8.12	What is SWL and size of closed chock and/or fairleads of enclosed type on stern:	64 Metric Tonnes	360X260
8.13	What is SWL of bollard on poopdeck suitable for escort tug:		74 Metric Tonnes
Bow/s	Stern Thruster		
8.14	What is brake horse power of bow thruster (if fitted):		0 Kilowatt
8.15	What is brake horse power of stern thruster (if fitted):		0 Kilowatt
Single	e Point Mooring (SPM) Equipment		
8.16	Does vessel comply with the latest edition of OCIMF 'Recommendations for Equipment Employed in the Mooring of Vessels at Single Point Moorings (SPM)':	Y	es
8.17	Is vessel fitted with chain stopper(s):	Yes	
8.18	How many chain stopper(s) are fitted:	1	
8.19	State type of chain stopper(s) fitted:	Tongue	
8.20	Safe Working Load (SWL) of chain stopper(s):	200 Metric Tonnes	
8.21	What is the maximum size chain diameter the bow stopper(s) can handle:	76 Millimetres	
8.22	Distance between the bow fairlead and chain stopper/bracket:	3,250 Millimetres	
8.23	Is bow chock and/or fairlead of enclosed type of OCIMF recommended size (600mm x 450mm)? If not, give details of size:	Yes	
Lifting	g Equipment	•	
8.24	Derrick / Crane description (Number, SWL and location):	Cranes: 1 x 10	Tonnes, Center
8.25	What is maximum outreach of cranes / derricks outboard of the ship's side:		6.885 Metres
Ship '	To Ship Transfer (STS)	I.	
8.26	Does vessel comply with recommendations contained in OCIMF/ICS Ship To Ship Transfer Guide (Petroleum or Liquified Gas, as applicable):	Y	es

9.	MISCELLANEOUS				
Engir	ne Room				
9.1	What type of fuel is used for main propulsion?	IFO 380CST			
9.2	What type of fuel is used in the generating plant?	IFO 380CST	IFO 380CST		
9.3	Capacity of bunker tanks - IFO and MDO/MGO:	1538.46 Cu. Metres	159 Cu. Metres 21 Cu. Metres		
9.4	Is vessel fitted with fixed or controllable pitch propeller(s)?	Fixed			
Insur	ance	•			
9.5	P & I Club - Full Style:	THE NORTH OF ENGLAND The North of England P & I Association, The Quayside, Newcastle upon Tyne, NE13DU UK Tel: 44-1912325221 Fax: 44-1912610540 Email: general@nepia.com Web: www.nepia.com			
9.6	P & I Club coverage - pollution liability coverage:	1,000,000,000 US\$			
Port S	State Control	•			

Q88.com Page 6 / 7

9.7	Date and place of last Port State Control inspection:	Nov 15, 2016 / Callao, Peru			
9.8	Any outstanding deficiencies as reported by any Port State Control:	No			
9.9	If yes, provide details:	NA			
Recent Operational History					
9.10	Has vessel been involved in a pollution, grounding, serious casualty or collision incident during the past 12 months? If yes, full description:	Pollution: No, N/A Grounding: No , N/A Serious casualty: No , Collision: No , N/A			
9.11	Last three cargoes / charterers / voyages (Last / 2nd Last / 3rd Last):	Private and Confidential as per Charter Party. Please contact owner for detail.			
Vetting					
9.12	Date/Place of last SIRE Inspection:	Apr 08, 2017 / Mollendo, Peru			
9.13	Date/Place of last CDI Inspection:	Dec 05, 2015 / Tuxpan, Mexico			
9.14	Recent Oil company inspections/screenings (To the best of owners knowledge and without guarantee of acceptance for future business)*:  * "Approvals" are not given by Oil Majors and ships are accepted for the voyage on a case by case basis.	REPSOL, PHILLIPS66, CDI			

Version 3 (www.Intertanko.com / www.Q88.com)

Form completed on http://www.q88.com/integration.aspx Please email support@q88.com an updated copy if this is not the latest version.

To the best of owners knowledge all information is true and given without any guarantee

Q88.com Page 7 / 7