

1.	VESSEL DESCRIPTION		
1.1	Date updated:	Feb 29, 2020	
1.2	Vessel's name:	MTM Vancouver	
1.3	IMO number:	9867607	
1.4	Vessel's previous name(s) and date(s) of change:	Not Applicable	
1.5	Date delivered:	Sep 20, 2019	
1.6	Builder (where built):	Shin Kurushima Dockyard Co. Ltd / Japan	
1.7	Flag:	Singapore	
1.8	Port of Registry:	Singapore	
1.9	Call sign:	9V6014	
1.10	Vessel's satcom phone number:	+1 9044504446 / +881677779729 / +1 9049006614 +1 9044387520	
	Vessel's fax number:	NA	
	Vessel's telex number:	NA	
	Vessel's email address:	master@vancouver.cruisecontrolmail.com	
1.11	Type of vessel:	Oil/Chemical Tanker	
1.12	Type of hull:	Double Hull	
Classification			
1.13	Classification society:	Nippon Kaiji Kyokai	
1.14	Class notation:	NK NS* (CSR, Tanker, Oils Flashpoint on and below 60°C and Chemicals Type II & III, PSPC-WBT,NC) (ESP)(IHM) MNS*	
1.15	If Classification society changed, name of previous society:	N/A	
1.16	If Classification society changed, date of change:	N/A	
1.17	IMO type, if applicable:	Type II & III	
1.18	Does the vessel have ice class? If yes, state what level:	No,	
1.19	Date / place of last dry-dock:	20 Sep 2019	Shin Kurushima Dockyard Co. Ltd.
1.20	Date next dry dock due	19 Sep 2022	
1.21	Date of last special survey / next survey due:	N/A	19 Sep 2024
1.22	Date of last annual survey:	N/A	
1.23	If ship has Condition Assessment Program (CAP), what is the latest overall rating:	NA	
1.24	Does the vessel have a statement of compliance issued under the provisions of the Condition Assessment Scheme (CAS): If yes, what is the expiry date?	N/A	
Dimensions			
1.25	Length Over All (LOA):	149.93 Metres	
1.26	Length Between Perpendiculars (LBP):	143.00 Metres	
1.27	Extreme breadth (Beam):	24.60 Metres	
1.28	Moulded depth:	13.20 Metres	
1.29	Keel to Masthead (KTM) / KTM in collapsed condition (if applicable):	39.87 Metres	
1.30	Bow to Center Manifold (BCM) / Stern to Center Manifold (SCM):	75.839 Metres	74.094 Metres
1.31	Distance bridge front to center of manifold:	45.129 Metres	
1.32	Parallel body distances:	Lightship	Normal Ballast Summer Dwt
	Forward to mid-point manifold:	22.851 Metres	23.747 Metres 23.751 Metres
	Aft to mid-point manifold:	15.664 Metres	23.810 Metres 35.671 Metres
	Parallel body length:	38.515 Metres	47.557 Metres 59.422 Metres
1.33	FWA at summer draft / TPC immersion at summer draft:	225 Millimetres	31.74 Metric Tonnes
1.34	What is the max height of mast above waterline (air draft)	Full Mast	Collapsed Mast
	Lightship:	34.790 Metres	0 Metres
	Normal ballast:	33.230 Metres	0 Metres
	At loaded summer deadweight:	29.703 Metres	0 Metres
Tonnages			
1.35	Net Tonnage:	6,544	

INTERTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 (Q88)

1.36	Gross Tonnage / Reduced Gross Tonnage (if applicable):	13,136	
1.37	Suez Canal Tonnage - Gross (SCGT) / Net (SCNT):	22,398.21	19,704.41
1.38	Panama Canal Net (PCNT):	17,679	

Loadline Information

1.39	Loadline Annex I	Freeboard	Draft	Deadweight	Displacement
	Summer:	3.069 Meters	10.167 Meters	22344 Metric Tonnes	28565 Metric Tonnes
	Winter:	3.280 Meters	9.956 Meters	21676 Metric Tonnes	27897 Metric Tonnes
	Tropical:	2.858 Meters	10.378 Meters	23016 Metric Tonnes	29237 Metric Tonnes
	Lightship:	10.719 Meters	2.517 Meters		6221 Metric Tonnes
	Normal Ballast Condition:	7.006 Meters	6.230 Meters	10321 Metric Tonnes	16542 Metric Tonnes

1.40	Does vessel have multiple SDWT?	NO
1.41	If yes, what is the maximum assigned deadweight?	NA

Ownership and Operation

1.42	Registered owner - Full style:	MTM Vancouver Pte. Ltd. 78 Shenton Way, #13-01, Singapore 079120 Tel: +65 6304 1770 Fax: +65 6220 7988 Email: marine@mtmsm.com
1.43	Technical operator - Full style:	M.T.M. Ship Management Pte. Ltd. 78 Shenton Way, #13-01, Singapore 079120 Tel: +65 63041770 Fax: +65 62207988 Email: marine@mtmsm.com Web: www.mtmshipmanagement.com Company IMO#: 1314037
1.44	Commercial operator - Full style:	M.T. Maritime Management (USA) LLC 2960 Post Road Southport, CT 06890, USA Tel: +1 203 226-7882 Fax: +1 203 226-8934 Email: operations@mtmaritime.com Web: www.mtmaritime.com
1.45	Disponent owner - Full style:	MTM Trading LLC Trust Company Complex, Ajeltake Island, Ajeltake Road, Majuro, Marshall Islands MH 96960

2.	CERTIFICATION	Issued	Last Annual or Intermediate	Expires
2.1	Safety Equipment Certificate:	20-Dec-2019	Not Applicable	19-Sep-2024
2.2	Safety Radio Certificate:	20-Dec-2019	Not Applicable	19-Sep-2024
2.3	Safety Construction Certificate:	20-Dec-2019	Not Applicable	19-Sep-2024
2.4	Loadline Certificate:	20-Dec-2019	Not Applicable	19-Sep-2024
2.5	International Oil Pollution Prevention Certificate (IOPPC):	20-Dec-2019	Not Applicable	19-Sep-2024
2.6	Safety Management Certificate (SMC):	12-Feb-2020	Not Applicable	11-Feb-2025
2.7	Document of Compliance (DOC):	28-Jun-2017	22-Aug-2019	16-Sep-2021
2.8	USCG (specify: COC, LOC or COI):	Not Applicable	Not Applicable	Not Applicable
2.9	Civil Liability Convention Certificate (CLC):	20-Feb-2020		20-Feb-2021
2.10	Civil Liability for Bunker Oil Pollution Damage Convention Certificate (CLBC):	20-Feb-2020		20-Feb-2021
2.11	U.S. Certificate of Financial Responsibility (COFR):	19-Sep-2019		19-Sep-2022
2.12	Certificate of Fitness (Chemicals):	20-Dec-2019	Not Applicable	19-Sep-2024
2.13	Certificate of Fitness (Gas):	Not Applicable	Not Applicable	Not Applicable
2.14	Certificate of Class:	20-Dec-2019	Not Applicable	19-Sep-2024

INTERTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 (Q88)

2.15	International Ship Security Certificate (ISSC):	12-Feb-2020	Not Applicable	11-Feb-2025
2.16	International Sewage Pollution Prevention Certificate (ISPPC)	20-Dec-2019		19-Sep-2024
2.17	International Air Pollution Prevention Certificate (IAPP):	20-Dec-2019	Not Applicable	19-Sep-2024

Documentation

2.18	Does vessel have all updated publications as listed in the Vessel Inspection Questionnaire, Chapter 2- Question 2.24, as applicable:		Yes
2.19	Owner warrant that vessel is member of ITOPF and will remain so for the entire duration of this voyage/contract:		Yes

3. CREW MANAGEMENT

3.1	Nationality of Master:	MYANMAR
3.2	Nationality of Officers:	MYANMAR
3.3	Nationality of Crew:	MYANMAR
3.4	If Officers/Crew employed by a Manning Agency - Full style:	Officers: N/A, Directly employed by Technical Operator Crew: N/A, directly employed by Technical Operator
3.5	What is the common working language onboard:	ENGLISH
3.6	Do officers speak and understand English:	Yes
3.7	In case of Flag Of Convenience, is the ITF Special Agreement on board:	Yes

4. HELICOPTERS

4.1	Can the ship comply with the ICS Helicopter Guidelines:	No
4.2	If Yes, state whether winching or landing area provided:	NA

5. FOR USA CALLS

5.1	Has the vessel Operator submitted a Vessel Spill Response Plan to the US Coast Guard which has been approved by official USCG letter:	Yes
5.2	Qualified individual (QI) - Full style:	O'Brien's Response Management 818 Town and Country Blvd., Suite 200, Houston, TX 77024 Tel: +1-281-606-4854 Fax: +1-281-320-9700 Email: vrp@wittobriens.com Web: www.wittobriens.com
5.3	Oil Spill Response Organization (OSRO) -Full style:	National Response Corporation 3500 Sunrise hwy Ste. T103 Great river, NY 11739, USA. Tel: +1.800.899.4672 Fax: +1.631.224.9086 Email: iocdo@nrcc.com
5.4	Has technical operator signed the SCIA / C-TPAT agreement with US customs concerning drug smuggling:	No

6. CARGO AND BALLAST HANDLING

Double Hull Vessels

6.1	Is vessel fitted with centerline bulkhead in all cargo tanks:	Yes
6.2	If Yes, is bulkhead solid or perforated:	SOLID SS 316 L

Cargo Tank Capacities

6.3	Capacity (98%) of each natural segregation with double valve (specify tanks):	Seg#1: 891.668 (1P) Seg#2: 882.531 (1S) Seg#3: 1209.146 (2P) Seg#4: 1209.363 (2S) Seg#5: 1370.127 (3P) Seg#6: 1369.909 (3S) Seg#7: 1404.191 (4P) Seg#8: 1404.408 (4S) Seg#9: 643.916 (5P) Seg#10: 655.201 (5S) Seg#11: 1403.947 (6P)
-----	---	--

INTERTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 (Q88)

		Seg#12: 1403.730 (6S) Seg#13: 1405.746 (7P) Seg#14: 1405.963 (7S) Seg#15: 1380.302 (8P) Seg#16: 1380.084 (8S) Seg#15: 1207.174 (9P) Seg#16: 1208.369 (9S) Slop: 424.026 (Slop P) Slop: 431.634 (Slop S)		
6.4	Total cubic capacity (98%, excluding slop tanks):	22237.600 Cu. Metres		
6.5	Slop tank(s) capacity (98%):	838.5468 Cu. Metres		
6.6	Residual/Retention oil tank(s) capacity (98%), if applicable:	51.0776 Cu meters		
6.7	Does vessel have Segregated Ballast Tanks (SBT) or Clean Ballast Tanks (CBT):	SBT		
SBT Vessels				
6.8	What is total capacity of SBT?	8082.570 Cu. Metres		
6.9	What percentage of SDWT can vessel maintain with SBT only:	36.17 %		
6.10	Does vessel meet the requirements of MARPOL Annex I Reg 18.2: (previously Reg 13.2)	Yes		
Cargo Handling				
6.11	How many grades/products can vessel load/discharge with double valve segregation:	20		
6.12	Maximum loading rate for homogenous cargo per manifold connection:	408.6 Cu. Metres/Hour		
6.13	Maximum loading rate for homogenous cargo loaded simultaneously through all manifolds:	3268.8 Cu. Metres/Hour		
6.14	Are there any cargo tank filling restrictions. If yes, please specify:	Yes p=1.30(Sloshing 1.85)		
Pumping Systems				
6.15	Pumps:	No.	Type	Capacity
	Cargo:	20	Framo	200 Cu M/Hr
	Stripping:			
	Eductors:			
	Ballast:	2	Framo	350 Cu M/hr
6.16	How many cargo pumps can be run simultaneously at full capacity:	5		
Cargo Control Room				
6.17	Is ship fitted with a Cargo Control Room (CCR):	Yes		
6.18	Can tank innage / ullage be read from the CCR:	Yes		
Gauging and Sampling				
6.19	Can ship operate under closed conditions in accordance with ISGOTT:	Yes		
6.20	What type of fixed closed tank gauging system is fitted:	RADAR TYPE (level echo) & Float type for 2 Slop Tanks		
6.21	Are overfill (high-high) alarms fitted? If Yes, indicate whether to all tanks or partial:	YES, ALL TANKS		
Vapor Emission Control				
6.22	Is a vapor return system (VRS) fitted:	Yes		
6.23	Number/size of VRS manifolds (per side):	2	200 Millimetres	
Venting				
6.24	State what type of venting system is fitted:	High Velocity PV (Press Vac)		
Cargo Manifolds				
6.25	Does vessel comply with the latest edition of the OCIMF 'Recommendations for Oil Tanker Manifolds and Associated Equipment':	YES		
6.26	What is the number of cargo connections per side:	20		
6.27	What is the size of cargo connections:	150 Millimetres		
6.28	What is the material of the manifold:	SUS 316L		
Manifold Arrangement				
6.29	Distance between cargo manifold centers:	500 Millimetres		
6.30	Distance ships rail to manifold:	3500 Millimetres		

INTERTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 (Q88)

6.31	Distance manifold to ships side:	3050 Millimetres	
6.32	Top of rail to center of manifold:	1961 Millimetres	
6.33	Distance main deck to center of manifold:	3050 Millimetres	
6.34	Manifold height above the waterline in normal ballast / at SDWT condition:	10.306Meters	6.119Meters
6.35	Number / size reducers:	2/ANSI 10" X JIS 8" 2/ANSI 10" X JIS 4" 2/JIS 8" X ANSI 6" 2ANSI 6" X JIS 4" 1/ANSI 12" X ANSI 10" 2/ANSI 10" X ANSI 8" 2/ANSI 10" X ANSI 6" 2/ANSI 8" X ANSI 6" 4/ANSI 6" X ANSI 4" 2/ANSI 10" X ANSI 8" 2/ANSI 8" X ANSI 6" 2ANSI 8" X ANSI 8"	

Stern Manifold

6.36	Is vessel fitted with a stern manifold:	No
6.37	If stern manifold fitted, state size:	NA

Cargo Heating

6.38	Type of cargo heating system?	Steam	
6.39	If fitted, are all tanks coiled?	Yes	
6.40	If fitted, what is the material of the heating coils:	SS316 L	
6.41	Maximum temperature cargo can be loaded/maintained:	90 C	75 C

Tank Coating

6.42	Are cargo, ballast and slop tanks coated?	Coated	Type	To What Extent
	Cargo tanks:	YES	Stainless Steel (SUS 316LN) & SUS Clad Steel(SUS316L)	Whole Tank
	Ballast tanks:	Yes	NTE HB x 2 (applied to PSPC)	Whole Tank
	Slop tanks:	Yes	Stainless Steel (SUS 316LN) & SUS Clad Steel(SUS316L)	Whole Tank
6.43	If fitted, what type of anodes are used:	NA		

7. INERT GAS AND CRUDE OIL WASHING

7.1	Is an Inert Gas System (IGS) fitted:	YES
7.2	Is IGS supplied by flue gas, inert gas (IG) generator and/or nitrogen:	NITROGEN GENERATOR
7.3	Is a Crude Oil Washing (COW) installation fitted:	N/A

8. MOORING

8.1	Mooring wires (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	N/A	N/A	N/A	N/A	N/A
	Main deck fwd:	N/A	N/A	N/A	N/A	N/A
	Main deck aft:	N/A	N/A	N/A	N/A	N/A
	Poop deck:	N/A	N/A	N/A	N/A	N/A
8.2	Wire tails	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	N/A	N/A	N/A	N/A	N/A
	Main deck fwd:	N/A	N/A	N/A	N/A	N/A
	Main deck aft:	N/A	N/A	N/A	N/A	N/A
	Poop deck:	N/A	N/A	N/A	N/A	N/A
8.3	Mooring ropes (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	6	60 Millimetres	Polypropylene and Polyester Composite	220 Metres	53.2 Metric Tonnes

INTERTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 (Q88)

	Main deck fwd:	N/A				
	Main deck aft:	N/A				
	Poop deck:	6	60 Millimetres	Polypropylene and Polyester Composite	220 Metres	53.2 Metric Tonnes
8.4	Other mooring lines	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	5	60 Millimetres	Polypropylene and Polyester Composite	200 Metres	53.2 Metric Tonnes
	Main deck fwd:	N/A	N/A	N/A	N/A	N/A
	Main deck aft:	N/A	N/A	N/A	N/A	N/A
	Poop deck:	4	60 Millimetres	Polypropylene and Polyester Composite	200 Metres	53.2 Metric Tonnes
8.5	Mooring winches			No.	# Drums	Brake Capacity
	Forecastle:	2		4		37.63 Tonnes
	Main deck fwd:	N/A				
	Main deck aft:	N/A				
	Poop deck:	2		4		37.63 Tonnes
8.6	Mooring bitts			No.		SWL
	Forecastle:	1		1		113 Metric Tonnes
		3		3		64 Metric Tonnes
		2		2		52 Metric Tonnes
	Main deck fwd:	2		2		64 Metric Tonnes
		2		2		52 Metric Tonnes
	Main deck aft:	2		2		64 Metric Tonnes
		2		2		52 Metric Tonnes
	Poop deck:	1		1		113 Metric Tonnes
		3		3		64 Metric Tonnes
		4		4		52 Metric Tonnes
8.7	Closed chocks and/or fairleads of enclosed type			No.		SWL
	Forecastle:	1		1		200 Metric Tonnes
		2		2		126 Metric Tonnes
	Main deck fwd:	2		2		89 Metric Tonnes
		2		2		80 Metric Tonnes
	Main deck aft:	2		2		80 Metric Tonnes
	Poop deck:	2		2		126 Metric Tonnes
		2		2		89 Metric Tonnes
		1		1		113 Metric Tonnes
Emergency Towing System						
8.8	Type / SWL of Emergency Towing system forward:				SC20-F/SP25-S	200 Metric Tonnes
8.9	Type / SWL of Emergency Towing system aft:				SC10A	102 Metric Tonnes
Anchors						
8.10	Number of shackles on port cable:					11
8.11	Number of shackles on starboard cable:					11
Escort Tug						
8.12	What is SWL and size of closed chock and/or fairleads of enclosed type on stern:				113 Metric Tonnes	250x450mm
8.13	What is SWL of bollard on poopdeck suitable for escort tug:					113 Metric Tonnes
Bow/Stern Thruster						
8.14	What is brake horse power of bow thruster (if fitted):				NA	
8.15	What is brake horse power of stern thruster (if fitted):				NA	
Single Point Mooring (SPM) Equipment						
8.16	Does vessel comply with the latest edition of OCIMF 'Recommendations for Equipment Employed in the Mooring of Vessels at Single Point Moorings (SPM)':					YES
8.17	Is vessel fitted with chain stopper(s):					YES
8.18	How many chain stopper(s) are fitted:				1	

INTERTANKO'S STANDARD TANKER CHARTERING QUESTIONNAIRE 88 (Q88)

8.19	State type of chain stopper(s) fitted:	TONGUE TYPE
8.20	Safe Working Load (SWL) of chain stopper(s):	200 Metric Tonnes
8.21	What is the maximum size chain diameter the bow stopper(s) can handle:	φ76
8.22	Distance between the bow fairlead and chain stopper/bracket:	3,607 Millimetres
8.23	Is bow chock and/or fairlead of enclosed type of OCIMF recommended size (600mm x 450mm)? If not, give details of size:	Yes
Lifting Equipment		
8.24	Derrick / Crane description (Number, SWL and location):	Cranes: 1 x 10 Tonnes, Midship
8.25	What is maximum outreach of cranes / derricks outboard of the ship's side:	4.7 Metres
Ship To Ship Transfer (STS)		
8.26	Does vessel comply with recommendations contained in OCIMF/ICS Ship To Ship Transfer Guide (Petroleum or Liquefied Gas, as applicable):	YES

9. MISCELLANEOUS
Engine Room

9.1	What type of fuel is used for main propulsion?	HFO 380 CST	
9.2	What type of fuel is used in the generating plant?	HFO & MGO	
9.3	Capacity of bunker tanks - IFO and MDO/MGO:	998.92 Cu. Metres	120.98 Cu. Metres
9.4	Is vessel fitted with fixed or controllable pitch propeller(s)?	Fixed propeller	

Insurance

9.5	P & I Club - Full Style:	The North of England Protecting & Indemnity Association Limited The Quayside, Newcastle upon Tyne, NE13DU UK Tel: +44(0)191 2325 221 Fax: +44 (0) 191 2610 540 Email: general@nepia.com Web: www.nepia.com	
9.6	P & I Club coverage - pollution liability coverage:	1,000,000,000 US\$	

Port State Control

9.7	Date and place of last Port State Control inspection:	13-Jan-2020 / Pivdennyi, Ukraine
9.8	Any outstanding deficiencies as reported by any Port State Control:	N/A
9.9	If yes, provide details:	N/A

Recent Operational History

9.10	Has vessel been involved in a pollution, grounding, serious casualty or collision incident during the past 12 months? If yes, full description:	N/A
9.11	Last three cargoes / charterers / voyages (Last / 2nd Last / 3rd Last):	Private and Confidential as per Charter Party. Please contact owner for detail.

Vetting

9.12	Date/Place of last SIRE Inspection:	16-Oct-2019 / Tuticorin
9.13	Date/Place of last CDI Inspection:	N/A
9.14	Recent Oil company inspections/screenings (To the best of owners knowledge and without guarantee of acceptance for future business)*: * "Approvals" are not given by Oil Majors and ships are accepted for the voyage on a case by case basis.	TOTAL

 Version 3 (www.Intertanko.com / www.Q88.com)

 Form completed on <http://www.q88.com/integration.aspx> Please email support@q88.com an updated copy if this is not the latest version.

To the best of owners knowledge all information is true and given without any guarantee